

# AUDIO-DINST Streaming Audio player with line out, KNXnet/IP, Trigger for 4 zones

Amati.linea Streaming Player is a high-fidelity, DIN-rail mounted audio solution designed for seamless integration into building automation systems.

## **Physical interfaces**

RJ45	1
Line-out pair	2 (RCA or clamp)
Triggers (zone control)	4 (24 V DC)
Reset button	1
USB 2.0	1

#### **Power**

Power supply	24 V DC via terminals
Power consumption	1.4 W

#### **Connections**

Power / Line-out / Triggers	Clamp, 0.8 mm <sup>2</sup> 1.5 mm <sup>2</sup>
Line-out	RCA

#### **Indicators**

LED 1	Green blinking – System load
LED 2	Off – Normal operation / Green – Reset

# **Enclosure**

Mounting support	DIN rail
DIN module width	3
Dimensions WxHxD	54 x 112 x 61 mm
IP degree of protection	IP20
Net weight	110 g

#### Standards compliance

EMC	EN61000-6-1; EN61000-6-3
LIVIO	LINO 1000-0-1, LINO 1000-0-3

#### **Environment**

Warranty	2 years
Relative humidity	0% 93% (without condensation)
Storage temperature	-15 °C +55 °C
Operational temperature	0 °C +45 °C
LITTIONICITE	



## **Key highlights**

Versatile Streaming Support Compatible with DLNA/UPnP servers, Spotify Connect (premium), AirPlay, FTP, NFS, HTTP servers, and includes 16GB of built-in media storage

# **High-Resolution Audio**

Supports lossless audio formats (ALAC/FLAC) with playback up to 24-bit/96kHz for superior sound quality

#### **Building Automation Integration:**

Equipped with KNXnet/IP and BACnet/IP protocols for seamless integration into smart building systems

# **Flexible Control Options**

Allows mapping of audio controls to KNX group addresses, enabling functions like radio channel switching and sound notifications via KNX push-buttons

## **Compact DIN-Rail Design**

Designed for easy installation in standard electrical cabinets, suitable for both residential and commercial setups





